

Buckingham Retractable Lanyards

The retractable lanyard automatically extends and retracts to allow user mobility. This unit utilizes an inertia-brake mechanism which locks when 5" of material pulls out per second to restrain the worker to a fall of less than 12". Meets all applicable ANSI standards.



Fall Arrest



Fall Restraint


5008	A	B	C	D	OPTIONAL
RETRACTABLE UNIT	LENGTH IN FEET	SWIVEL	(Hardware for both ends except when noted) CONNECTING DEVICE-FRAME END	CONNECTING DEVICE-LANYARD END	OPTIONS
	6'	0 = NONE	0 = 1" dia. Integral loop with wear piece	F = 1 3/4" ret. lanyard bracket (frame end only)	A1 = Rubber boot for carabiner
	8'	3 = 5/16 Swivel w/Bolt & Nut	2 = dee ring	L = 1705 lock snap	K = Signifies Buck Stop Pack only Attached to lanyard end
	10'		3 = steel carabiner triple lock	P = retrieval dee ring	
			8 = 704 swivel snap	R = 3130 2 1/2" ladder hook	
			9 = 2 1/4" ladder hook	S = black powder coated retrieval dee ring	
			+1 = Attached to 3809R by means of 'F' bracket (frame end only)	T = 7 1/2" captive eye rebar hook	
			+2 = 5555SA carabiner	U = alum. carabiner w/ eye	
			+3 = 5005L1 carabiner	V = 1706 locking snap	
			+4 = 2 1/2" ladder hook stamped	X = 1 1/2" dia integral loop w/ wear piece	
			+6 = Lock rope snap, alum. body -stamped	Z = 3129 ladder hook 1 3/4"	
			+7 = lock rope snap stamped	+B = 99E locking snap hook	
			A = alum. carabiner 5005SA self-locking	+C = small lock ladder hook	
			B = 3034 large ladder snap	+D = 2" ret. lanyard bracket (frame end only)	
			D = steel carabiner 5005 self-lock	+N = Attac carabiner 223516	
			E = quick link (frame end only)	+Z = Hardware meets Z359.1 (3600 lbs gate)	



Model 5008-83EV



Swivel (B Option)
Option3 - with Bolts




Body Belt Mounting Bracket:
Option F - fits 1 3/4" belt strap.
Option +D - fits 2" belt strap.

Popular Models



5008-103EV



Protective Steel Bracket

Dust Cover



5008-80FV

Steel Bracket protects the internal components; available on 8' models only.

Dust Cover prevents web from twisting inside the unit.



5008-80+1V Retractable Lanyard
For use in an aerial lift truck. Attaches directly to boom.



5008-83RV



Ratchet Boom Strap Model 3809R
(5000 lbs. rated)
The ratchet boom strap provides a secure anchor on the bucket truck boom.



1706 17061

1706 (Option V); Locking Rope Snap: 1" (25mm) eye, 15/16" opening, 6" (152mm) long. Rated to 5000 lbf. (22kn) **or, when using suffix +Z in part number, Model 17061 Swivel Locking Rope Snap (shown on right) with a 3600 lb gate load**



3130

31301

3130 (Option R); Large Locking Ladder Snap: 1" (25mm) eye (I.D.), 2.5" (63.5mm) opening, 9 3/4" (248mm) length, 1 lb. 8 oz. weight. Rated to 5000 lbf. (22kn) **or when using suffix +Z in part number, Model 31301 Locking Ladder Snap (shown on right) with a 3600 lb gate load.**



1709

17091

1709 (Option +7); Locking Rope Snap [1" (25mm) eye (I.D.), 3/4" (19mm) opening, 6 1/8" (156mm) length, 10.2 oz. (290gm) weight. Min. tensile strength 5000 lbs. (22kn)] **or, when using suffix +Z in part number, model 17091 Locking Rope Snap with a 3600 lb gate load.**



Indicates meets ANSI Z359.1-2007 standard.



5005SAE (Option U); Auto Lock Aluminum Carabiner with eye: .71" (18mm) opening; 5 1/4" (133mm) length; Rated to 5620 lbs (25kn)



1705 (Option L) Locking Rope Snap [1" (25mm) eye (I.D.), .812" (20.6mm) opening (keeper to bill in open position), 5 1/2" (140mm) length, 9.6 oz weight. Rated to 5000 lbf. (22kn) **or, when using suffix +Z in part number, Model 17051 Locking Rope Snap (not shown) with a 3600 lb gate load.**



1711 (Option +K); Alloy Steel RotoSnap: .670" (17mm) gate opening, 5 3/16" (132mm) long, 11.2 oz. weight. Min. tensile strength 10,000 lbs. and min. gate/side load 5000 lbs



30341 (Option +H); Large Locking Rebar Hook: 15/16" (24mm) eye (I.D.), 3 11/32" (85mm) opening, 13" (330mm) length. Rated to 3968 lbf. (17kn). Meets 5000 lb. rating. Only to be used on shock absorbing style lanyards.



1710 (Option +N); Locking Aluminum Snap: .75" (19mm) eye (I.D.), .875" (22mm) opening, 5.375" (137mm) length. Rated to 7,200 pounds (32.7kn)

3035

30351



3035 (Option +4); Locking Ladder Snap: 1" (25mm) eye (I.D.), 2.25" (57mm) opening, 8.75" (222mm) length, 1 lb. 4 oz. weigh. Rated to 5000 lbf. (22kn) **or, when using suffix +Z in part number, Model 30351 Locking Rope Snap with a 3600 lb gate load.**



3129 (Option Z); Small Locking Ladder Snap: 1" (25mm) eye (I.D.), 1.750" (44.5mm) opening, 8 1/8" (206mm) length, 1 lb. 3 oz. weight. Rated to 5,000 pounds (22kn)



1708 (Option +6); Aluminum Body Locking Rope Snap Hook: 7/8" (22mm) eye (I.D.), .718" (18mm) opening, 5 1/4" (133mm) length, 5.4 oz. (154gm) weight. Min. tensile strength 5600 lbs. (24kn)

Carabiners



5005SA (Option A) Auto Lock Aluminum Carabiner

Length – 4 1/2" (114mm)
Opening – 3/4" (19mm)
Breaking Strength – 6700 lbf (30kn)



5005L2 Steel Twist Lock Carabiner

Length – 7 1/8" [178mm]
Opening – 1 1/8" [28mm]
Breaking Strength – 10,120 lbs. (45kn)



5005 (Option D) Auto Lock Steel Carabiner
Length – 5" (127mm), Opening – 1" (25mm)
Breaking Strength – 6351 lbf (28kn)
or, when using suffix +Z in part number, Option D uses Model 50051 Auto Lock Steel Carabiner with a 3600 lb gate load.



5005M Screw Gate Steel Carabiner*

Length – 4 1/2" (114mm)
Opening – 1" (25mm)
Breaking Strength – 11,240 lbs.



5005T Twist Lock Steel Carabiner

Length – 4 1/4" (108mm)
Opening – 1" (25mm)
Breaking Strength – 8,992 lbs.



5005L1 Steel Twist Lock Carabiner

Length – 9" (225mm)
Opening – 2" (51mm)
Breaking Strength – 9,220 lbs. (41kn)



5005K Steel Auto Lock Carabiner

Length – 4 1/2" (113mm)
Opening – 1" (25mm)
Breaking Strength – 6,747 lbs. (30kn)



5555WS1 Tri-Act Carabiner

Length – 4 5/8" (115mm)
Opening – 1" (25mm)
Breaking Strength – 5,625 lbs. (25kn)



5555SA Ball Lock Aluminum Carabiner (Option +2)

Length – 4.25" (108 mm)
Opening – .826" (21 mm)
Breaking Strength – 6,295 lbs. (28 kn.)



5555WSA William Ball Lock Aluminum Carabiner

Length – 4 5/8" (115mm)
Opening – 1" (25mm)
Breaking Strength – 5,625 lbs. (25kn)



5555S1 AM'D Aluminum Carabiner

Length – 4.25" (108 mm)
Opening – .826" (21 mm)
Breaking Strength – 6,295 lbs. (28 kn.)



1711 (Option +K); Alloy Steel RotoSnap: .670" (17mm) gate opening, 5 3/16" (132mm) long, 11.2 oz. weight. Min. tensile strength 10,000 lbs. and min. gate/side load 5000 lbs



Indicates meets ANSI Z359.1-2007 standard.

***WARNING: NOT INTENDED FOR HUMAN SUPPORT OR FALL PROTECTION**